

SKYJACKER® WHEEL & TIRE SPECIFICATIONS

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
Chevrolet / GM / GMC							
06-08	K1500, Avalanche, Tahoe, SUV, Etc.(Coil-Over Assembly) ^{1,2,3}	2"	265	75	16"	8"	OEM
		3"	285	75	16"	8"	4.5"
		6"	315	75	16"	8"	4.5"
00-05	Cadillac Escalade, ESV, EXT ^{1,3}	3"	285	75	16"/17"	8"	4.5"
04-08	Colorado/Canyon 4WD ²	4"	285	75	17"	8"	4.75"
00-05	Tahoe/Yukon/Suburban 4WD ²	3"	285	75	16"	8"	4.5"
		6"	285	75	16"	8"	4.5"
00-05	Denali/Yukon XL 4WD ²	3"	285	75	16"	8"	4.5"
02-05	Avalanche 4WD ²	3"	285	75	16"	8"	4.5"
		6"	315	75	16"	8"	4"
02-08	Hummer H2 4WD	5.5"	38"	12.5"	17"	9"	4.5"
01-07	GM 2500HD 4WD ^{2,3}	3"	285	75	16"	8"	4"
01-05	1500HD, 2500, 2500HD 4WD ²	6"	315	75	16"	8"	4"
99-06	K1500 IFS 4WD ^{2,3}	3"	285	75	16"	8"	4.5"
		6"	315	75	16"	8"	4.5"
88-98	Full-Size IFS 4WD ²	2.5"	285	75	15"	8-9"	4.5"
		6"	35"	12.5"	15"-16"	8-9"	4.5"
88-91	Full-Size Blazer, Jimmy, Suburban 4WD	2.5"	33"	12.5"	15"-16"	8-9"	3.5"- 4"
		4"	35"	12.5"	15"-16"	8-9"	3.5"- 4"
		6"	37"	12.5"	15"-16"	8-9"	3.5"- 4"
		8"	39"	12.5"	15"-16"	10"	3.5"- 4"
73-87	Full-Size 4WD	2.5"	33"	12.5"	15"-16"	10"	3.5"- 4"
		4"	35"	12.5"	15"-16"	10"	3.5"- 4"
		6"	37"	12.5"	15"-16"	10"	3.5"- 4"
		8"	39"	12.5"	15"-16"	10"	3.5"- 4"
67-72	Full-Size 4WD	2.5"	34"	12.5"	15"-16"	10"	3.5"- 4"
		4"	36"	12.5"	15"-16"	10"	3.5"- 4"
		6"	38"	12.5"	15"-16"	10"	3.5"- 4"
		8"	40"	12.5"	15"-16"	10"	3.5"- 4"
DODGE							
06-07	Ram Pickup 1500 4WD ³	2"	33	12.5"	17"	9"	OEM
02-05	Ram Pickup 1500 4WD ²	6"	37"	12.5"	17"	9"	5"
03-08	Ram 2500, 3500 Pickup 4WD Mega Cab ²	3"	34"	12.5"	15"-16"	10"	4.625"
		5"	37"	12.5"	15"-16"	10"	4.625"
94-01	Ram Pickup 4WD	2"-3"	33"	12.5"	15"-16"	10"	4.625"
		4"-5"	35"	12.5"	15"-16"	10"	4.625"
		7"	38"	12.5"	15"-16"	10"	4.625"
61-93	Full-Size 1500, 2500 4WD	2"	33"	12.5"	15"-16"	10"	4"
		4"	35"	12.5"	15"-16"	10"	4"
		6"	37"	12.5"	15"-16"	10"	4"
		8"	39"	12.5"	15"-16"	10"	4"
FORD F-150, Bronco, Expedition							
04-08	F-150 4WD, 2WD ^{2,3}	2"-3"	285	75	16"	8"	4.5"
04-08	F-150 4WD, 2WD ²	6"	315	75	16"	8"	4.5"
97-03	F-150 4WD	6"	35"	12.5"	16"	8"	4.5"

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
92-96	F-150, Bronco 4WD, 2WD	2"	32"	12.5"	15"	10"	4"
		4"	33"	12.5"	15"	10"	4"
		6"	35"	12.5"	15"	10"	4"
		8"	37"	12.5"	15"	10"	4"
87-91	F-150, Bronco 4WD, 2WD	2"	34"	12.5"	15"	10"	4"
		4"	36"	12.5"	15"	10"	4"
		6"	38"	12.5"	15"	10"	4"
80-86	F-150, Bronco 4WD, 2WD	2"	33"	12.5"	15"	10"	4"
		4"	35"	12.5"	15"	10"	4"
		6"	37"	12.5"	15"	10"	4"
69-79	F-150, 78-79 Bronco 4WD	2"	33"	12.5"	15"	10"	4"
		4"	35"	12.5"	15"	10"	4"
		6"	37"	12.5"	15"	10"	4"
66-77	Bronco 4WD with Cut-Outs	3"	33"	12.5"	15"	10"	4"
		5"	35"	12.5"	15"	10"	4"
		7"	37"	12.5"	15"	10"	4"
03	Expedition 4WD	2"	32"	11.5"	16"	8"	3.625"
FORD 66-08 F-250, F-350							
05-08	F-250, F-350 4WD Super Duty ²	1"	32"	12.5"	16.5"	9.75"	4.625"
		2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	36"	12.5"	16.5"	9.75"	4.625"
		8.5"	38"	12.5"	16.5"	9.75"	4.625"
99-04	F-250, F-350 4WD Super Duty	2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	36"	12.5"	16.5"	9.75"	4.625"
		8"	38"	12.5"	16.5"	9.75"	4.625"
92-98	F-350 4WD Mono Beam	2"	34"	12.5"	16.5"	9.75"	4.625"
		4"	36"	12.5"	16.5"	9.75"	4.625"
		6"	38"	12.5"	16.5"	9.75"	4.625"
86-91	F-350 4WD Mono Beam	2"	36"	12.5"	16.5"	9.75"	4.625"
		4"	38"	12.5"	16.5"	9.75"	4.625"
		6"	40"	12.5"	16.5"	9.75"	4.625"
FORD 66-08 F-250, F-350 continued...							
92-98	F-250 4WD Twin I Beam	2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	37"	12.5"	16.5"	9.75"	4.625"
80-91	F-250, F-350 4WD Twin I Beam	2"	33"	12.5"	16.5"	9.75"	4.625"
		4"	35"	12.5"	16.5"	9.75"	4.625"
		6"	37"	12.5"	16.5"	9.75"	4.625"
92-96	F-250, F-350 2WD	2"	32"	12.5"	16"	8"	3.75"
		4"	34"	12.5"	16"	8"	3.75"
		6"	36"	12.5"	16"	8"	3.75"
78-79	F-250 Low Boy 4WD	2"	35"	12.5"	16.5"	9.75"	3.75"
		4"	37"	12.5"	16.5"	9.75"	3.75"
		6"	40"	12.5"	16.5"	9.75"	3.75"
66-77	F-250 High Boy 4WD	2"	38"	12.5"	16.5"	9.75"	3.75"
		4"	40"	12.5"	16.5"	9.75"	3.75"

SKYJACKER® WHEEL & TIRE SPECIFICATIONS

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
FORD Ranger, Bronco II, Explorer, Navajo							
93-97	Ranger 4WD	2"	32"	12.5"	15"	8"	4"
		4"	33"	12.5"	15"	8"	4"
		6"	34"	12.5"	15"	8"	4"
		8"	36"	12.5"	15"	8"	4"
90-94	Explorer, Navajo 4WD	2"	31"	12.5"	15"	8"	4"
83-92	Ranger, Bronco II 4WD	2"	28"	12.5"	15"	8"	4"
		4"	30"	12.5"	15"	8"	4"
		6"	32"	12.5"	15"	8"	4"
HONDA							
06-08	Ridgeline 4WD ²	2"	275	60	17"	8"	5"
72-82	Scout II 4WD	2"	31"	12.50"	15"	8"	3.75"
72-82	Scout II 4WD	4"	33"	12.50"	15"	8"	3.75"
ISUZU							
05-06	Isuzu i-Series	4"	285	75	17"	8"	4.75"
JEEP							
07-08	Wrangler JK 2-Door & 4-Door ^{1,2}	2"	33"	12.5"	16"	8"	4.5
		2.5-3.5"	305	75	16"	8"	4.5
		4-5"	35"	12.5"	16"	8"	4.5
		6-7"	37"	12.5"	16"	8"	4.5
04-06	Wrangler Unlimited, Rubicon	2"	32"	11.5"	15"	8"	3.75"
		4"	34"	12.5"	15"	8"	3.75"
		6"	35"	12.5"	15"	10"	3.75"
		8"	37"	12.5"	15"	10"	3.75"
97-03	Wrangler TJ	2"	32"	11.5"	15"	8"	3.75"
		4"	34"	12.5"	15"	8"	3.75"
		6"	35"	12.5"	15"	10"	3.75"
		8"	37"	12.5"	15"	10"	3.75"
		10"	38"	12.5"	15"	10"	3.75"
87-96	Wrangler YJ	2"	31"	10.5"	15"	8"	3.75"
		4"	33"	12.5"	15"	8"	3.75"
		6"	35"	12.5"	15"	8"	3.75"
55-86	CJ and Scrambler	2"	31"	12.5"	15"	8"	3.75"
		4"	33"	12.5"	15"	10"	3.75"
05-07	Grand Cherokee WK 4WD, 2WD ²	2"	245	70	17"	8"	OEM
99-01	Grand Cherokee WJ 4WD	2"	31"	10.5"	16"	8"	3.75"
93-98	Grand Cherokee ZJ 4WD, 2WD	3"	31"	10.5"	15"	8"	3.75"
02-06	Liberty 4WD, 2WD ¹	2.5"	30"	10.5"	16"	8"	5"
84-01	Cherokee XJ 4WD, 2WD	2"	30"	9.5"	15"	7"	3.75"
		3"	31"	10.5"	15"	8"	3.75"
		6"	33"	12.5"	15"	8"	3.75"
		8"	35"	12.5"	15"	8"	3.75"
05-07	Jeep Commander XK ²	2"	245	70	17"	8"	OEM
86-92	Comanche 4WD, 2WD	3"	31"	10.5"	15"	8"	3.75"
74-91	J10, J20, Cherokee, Wagoneer	4"	35"	12.5"	15"	10"	3.75"
NISSAN							
04-07	Titan 4WD ²	2.5"	285	75	18"	7"	5
04-05	Armada 4WD ²	2.5"	285	75	18"	7"	5

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Offset
TOYOTA							
07-08	FJ Cruiser ²	2"	265	75	17"	8"	OEM
		3"	285	75	17"	8"	4.5
01-04	Sequoia 4WD	2.5"	32"	11.5"	16"	8"	3.5"
00-07	Tundra 4WD	2"	32"	11.5"	16"	8"	3.5"
00-07	Tundra 4WD	3"	32"	11.5"	16"	8"	3.5"
2007	Tundra 4WD	6"	35"	12.5"	16"	8"	3.5"
05-07	Tacoma 4WD, Pre-Runner 2WD ²	2"	31"	11.5	16	8"	4.5"
		2.5"-3"	285	75	16"	8"	4.5"
96-04	Tacoma 4WD, Pre-Runner 2WD	2.5"-3"	31"	10.5"	15"	8"	3.5"
86-95	IFS Pickup 4WD	4"	33"	12.5"	15"	8"	3.75"
96-01	4Runner 4WD	2.5"	31"	11.50"	15"	8"	3.5"
84-85	Pickup, 4Runner 4WD	3"	33"	12.5"	15"	8"	3.75"
		5"	35"	12.5"	15"	8"	3.75"
		7"	37"	12.5"	15"	8"	3.75"
79-83	Pickup, 4Runner 4WD	3"	35"	12.5"	15"	8"	3.75"
		5"	37"	12.5"	15"	8"	3.75"
		7"	39"	12.5"	15"	8"	3.75"
91-97	FJ80 LandCruiser 4WD	2.5"	33"	12.5"	15"	8"	3.75"
64-80	LandCruiser 4WD	2"	32"	12.5"	15"	8"	3.75"
		4"	35"	12.5"	15"	8"	3.75"
¹ Footnote: Requires minor trimming.							
² Footnote: If you change the Tire Diameter/Wheel Size on this application, you must still maintain the equivalent 'Section Width' and 'Overall Diameter' to the 'Height' and 'Width' dimensions listed in the chart.							
³ Footnote: Can use OEM Wheel							

NOTE: This Chart is to be Used Strictly as a REFERENCE Due to Actual Lift Heights and Variances in Tire Sizes from Various Manufacturers.